



K Series

# K-700L





K Series

**K-700L**

<b>Optical system</b>	Common Main Objective (CMO) Infinity optical system
<b>Observation tube</b>	Binocular head
<b>Inclination</b>	45° inclined
<b>Interpupillary distance</b>	54-76mm
<b>Diopter adjustment</b>	On both tubes, +/- 5 diopter
<b>Eyepieces</b>	Widefield WF10X/23mm
<b>Objectives system</b>	Zoom, ratio 5.2:1
<b>Objectives</b>	0.6X~3.1X
<b>Working distance</b>	89mm
<b>Stand type</b>	Pole type stand with transmitted illumination
<b>Head holder</b>	For Ø32mm column with incident illumination
<b>Focus mechanism</b>	Coarse focusing system with tension adjustment
<b>Focusing stroke</b>	49mm
<b>Incident illumination</b>	Halogen 12V/10W with intensity control
<b>Transmitted illumination</b>	Halogen 12V/10W with intensity control
<b>Transformer</b>	Internal
<b>Power supply</b>	100-240V (CE)
<b>Accessories included</b>	Dust cover, black/white and frosted stage plates and blue filter
<b>Dimensions LxWxH</b>	329x277x434mm
<b>Base</b>	329x277mm
<b>Column/Arm</b>	Height 295mm, Ø32mm
<b>Net weight</b>	5.9kg