

MX-T6-Pro

LCD Digital Tube Roller

Features

- LCD displays the speed and time
- Rocking & rolling at variable-speed
- Adjustable speed range from 10 to 70 rpm
- Six roller design for gentle and efficient rolling, and easy to clean
- DC brushless motor quiet and maintenance free
- Cold room and incubator compatible



LCD display



Timer



MX-T6-S

Standard tube roller

Features

- Adjustable speed range from 0 to 70 rpm
- Six roller design for gentle and efficient rolling, and is easy to clean

Applications

DLAB laboratory tube rollers provide a gentle and highly efficient rolling motions, deal for mixing blood samples, viscous substances and liquid-solid suspensions. Used in a variety of applications, such as the prevention of blood coagulation, immune precipitation, etc.

Specifications	MX-T6-Pro	MX-T6-S+
Amplitude	24mm	24mm
Motor type	Brushless DC motor	Brushless DC motor
Rocking motion	Rocking and rolling	Rocking and rolling
Max. load capacity	4kg	4kg
Number of rollers	6	6
Roller size[length]	280mm	280mm
Speed range	10 -70rpm	0-70rpm
Speed display	LCD	Scale
Timer	Yes	-
Timer display	LCD	-
Time setting range	1-1199min	-
Operation mode	Continuous/timer	Continuous
Voltage,Frequency	100-240V,50/60Hz	100-240V,50/60Hz
Power	30W	25W
Dimension [D×W×H]	485×250×100mm	485×250×100mm
Weight	5.1kg	4.5kg
Permissible ambient temperature and humidity	5-40°C,80%RH	5-40°C,80%RH
Protection class	IP21	IP21